Contactor Panels – Data Sheet

WS 100 and 200 Contactor Panels

GENERAL PRODUCT INFORMATION

The contactor panels are designed for snow and ice melting applications. All panels are pre-wired and UL listed complete with a NEMA 4 weatherproof enclosure, wiring diagram, terminal connection block, and two or four 3-pole contactors. The panel can be activated by Warmzone's in-ground sensor, aerial sensor, or optional integrated start/stop timer.

FEATURES INCLUDE:

- Easy to install
- NEMA 4 weatherproof, UL listed panel box
- Pre-wired terminal connections
- LED "heat on" indicator
- Low cost
- Optional integrated timer start/stop
- 2-year limited warranty



WS100 contactor panel.

TECHNICAL DATA

Power Voltage Range:	120 - 600 VAC
Maximum Continuous Amperes (Heating Load)	100A / 200A
Control Voltage:	120 volt
Enclosure Type:	NEMA 4 weatherproof enclosure
Mounting:	Wall-mounted (indoor or outdoor)
Dimensions (H x W x D): 100 amp 200 amp	 12 x 10 x 5 (305mm x 254mm x 127mm) 16 x 14 x 6 (406mm x 356mm x 152mm)



Contactor panel



Contactor panel with timer

WARRANTY INFORMATION

Contactor Panel: 2-year limited warranty.

TECHNICAL SUPPORT

For technical questions, please contact Warmzone at 888.488.WARM (9276) or via the web, www.warmzone.com.

Warmzone accepts no responsibility for possible errors in catalogs, brochures, other printed materials, and website information. Warmzone reserves the right to alter its products without notice. This also applies to products already on order provided that such alteration can be made without subsequent changes being necessary in specifications already agreed upon. All trademarks in this material are property of the respective companies. All rights reserved.