240 Amp Relay Panels – Data Sheet

Relay Panels (with optional GFEP) GENERAL PRODUCT INFORMATION

Relay Panel – The relay panels are designed for snow and ice melting applications. All panels are pre-wired and UL listed complete with a NEMA 4 enclosure, wiring diagram, terminal connection block, and eight 2-pole relays. Timer panels can be used stand alone or in conjunction with an automatic controller. Relay panels must be used in conjunction with an automatic controller.

FEATURES INCLUDE:

- Easy to install
- NEMA 4, weatherproof UL listed panel box
- Optional integrated 10-100mA GFEP
- LED trip indicator (internal)
- LED "heat on" indicator light
- Pre-wired terminal connections
- 2-year limited warranty



240 amp relay panel

TECHNICAL DATA

Power Voltage Range:	120 - 277 VAC
Maximum Heating Load:	120A / 240A
Switching Relays:	2-pole 30A
Protection:	120 volt
Operating Temperature Range:	-30°F to 131°F
Storage Temperature Range:	-40°F to 185°F
Relative Humidity:	0% to 95% non-condensing
Approvals:	cULus Listed
Enclosure Type:	NEMA 4 weatherproof
Mounting:	Wall-mounted (indoor or outdoor)
Optional Ground Fault Equipment Protection:	Adjustable Ground Fault Relay 10-100mA
Dimensions (H x W x D): Without GFEP With GFEP	 16 x 20 x 6 (406mm x 508mm x 152mm) 20 x 20 x 6 (508mm x 508mm x 152mm)

WARRANTY INFORMATION

Relay Panel: 2-year limited warranty.

TECHNICAL SUPPORT

For technical questions, please contact Warmzone at 888.488.WARM (9276) or via the web, www.warmzone.com.

Warmzone accepts no responsibility for possible errors in catalogs, brochures, other printed materials, and website information. Warmzone reserves the right to alter its products without notice. This also applies to products already on order provided that such alteration can be made without subsequent changes being necessary in specifications already agreed upon. All trademarks in this material are property of the respective companies. All rights reserved.